

FIBER CONNECTOR & FERRULE STYLE OVEN

一體式和散件式光纖連接器烘烤機

MODEL NO. : **HT-310**



Feature

- Special designed for curing epoxy of fiber ferrule & connectors.
- 30 connectors can be placed for heating at the same time.
- Suitable to different type of connectors, change the heating block to save cost.
- Two set of ferrule heating plates are supplied to control and operate independently.
- Ferrule heating plates can be supplied subject to demand of specific outer jacket and varied type of connectors.
- Individual heating timing control, the alarm will remind operator when heating is done, the auto pusher will secure heating quality.

Specification

Machine size	320W x 370L x 220H mm
Net weight	12 KG
Power	AC 110 / 220V , 50/60 Hz , 600W
Consumption air	5 kgf/cm ²
Heating temperature	199 °C (Max.)
Time setting	99 Min. 59 Sec. (Max.)
Connector heat block	30 Position , Connector Type Available .
Ferrule heat Plate	2 Sets.
Carton Dimension	56W x 38L x 56H cm



HT-310-250



HT-310-125



HT-310-MTRJ



HT-310-SC



HT-310-LC

Order

HT-310-1	Power : 110 V
HT-310-2	Power : 220 V
HT-310-SC	Standard Block , For FC / SC / ST Connectors
HT-310-LC	Heating Block , For LC Connectors
HT-310-250	Heating Plate , For ϕ 2.5 mm ferrule
HT-310-125	Heating Plate , For ϕ 1.25 mm ferrule
HT-310-MTRJ	Heating Plate , For MTRJ ferrule