

FC CONNECTOR

光纖連接器零件

PART NO. :



Specification

		SM	MM
Insertion Loss	Premium UPC	0.08dB typical	0.15dB
	Premium APC	0.10dB typical	
	Standard connector	0.12dB typical	0.20dB
Return Loss		≥55dB typical (PC) ≥68dB typical (APC)	
Durability		< 0.1dB typical Change , 500 matings	
Operating Temperature		-40°C to +75°C	
Ferrule Hole Sizes		125.5μm +1/-0, Concentricity: ≤ 1μm	127μm (MM)

Order

FC- A B C D - 300

A

Connector

B

Ferrule

C

Boot Type

D

Boot Color

1 : Pre-Assembled

1 : SM

1 : 3.0 mm cable standard

1 : Blue **4** : Yellow

2 : Unassembled

2 : MM

2 : 2.0 mm cable standard

2 : Black **5** : Beige

3 : 0.9 mm fiber boot

3 : Red

AFC- A B C D - 300

A

Connector

B

Ferrule

C

Boot Type

D

Boot Color

1 : Pre-Assembled

1 : Cone

1 : 3.0 mm cable standard

1 : Green

2 : Unassembled

2 : Step

2 : 2.0 mm cable standard

3 : 8° Pre-Angled

3 : 0.9 mm fiber boot

FC CONNECTOR

光纖連接器零件

PART NO. :

